



Quality, service, and customer satisfaction is our driving force.



AFRIQ EP 2 L GREASE

DESCRIPTION

High quality Lithium-Base Greases blended from solvent-refined oils and incorporates corrosion and oxidation-inhibitors.

They have outstanding chemical stability under severe working conditions and operating temperatures of 10 °C to 130 °C.

Their resistance to oil separation and water is very good making them ideal under moist and corrosive conditions.

They are formulated using medium viscosity mineral oil, Lithium 12 Hydroxystearate soap and fortified with additives to enhance oxidation, stability and prevent rust.

APPLICATION

Ep 2 L Grease is recommended for the lubrication of anti-friction, plain, ball and roller bearings in all types of machinery such as electric motors, generators and mechanisms having ferrous and non-ferrous bearings. Their low starting torque characteristics make it ideal grease for electric motor bearings.

BENEFITS

- One grease for a wide variety of Industrial requirements.
- Resist to water wash.
- Good dispensing characteristics.
- Long service life.
- Excellent rust protection.
- Greater reliability.
- Wide application range.

TYPICAL CHARACTERISTICS

Thickening Agent	Lithium 12 Hydroxystearate
NLGI Classification	2
Worked Penetration @ 25 °C	265-295
Drop Point °C	180
Oil Viscosity @ 40 °C cst	180-210
Rust Prevention	1
Recommended Temp. Range	120
Colour, Visual	Dark Brown