



Quality, service, and customer satisfaction is our driving force.

## AFRIQ 20W50 SG CD

### DESCRIPTION

Afriq Lube 20W50 is a robust heavy duty engine crankcase oil suitable for use in older, high mileage mixed fleets of cars, mini bus taxis, light commercial vehicles and contractor equipment where oil consumption is of concern. It provides benefits during starting and warm-up as well as the advantages of multigrade oil. Being SAE 20W40 viscosity oil it gives good high temperature performance by providing a thicker oil film on bearing surfaces as well as better sealing of piston rings. It exceeds API Service Classification SG/CD.

### APPLICATION

Afriq Lube 20W50 is recommended for older naturally aspirated petrol and diesel engines of passenger cars, mini bus taxis, light commercial vehicles and contractor equipment involved in start/stop operations with short service intervals. It can also be used as a non-extreme pressure gear lubricant where engine oils of the same quality and viscosity range are recommended. Afriq Lube 20W50 should not be used in extended service applications. Always consult the manufacturers operating manual to confirm the suitability of the lubricant for a particular vehicle.

### PERFORMANCE LEVELS

- API SG/CD

### BENEFITS

- Excellent protection against wear and corrosion.
- Keeps engines clean.
- Reduces oil consumption.
- Maintains optimum viscosity at all temperatures.
- Smooth engine operation

### KEY PROPERTIES

TYPICAL PHYSICAL CHARACTERISTICS	
SAE	20W50



Viscosity at 40 °C	175
Viscosity at 100 °C	19,4
Viscosity Index	127
Pour Point °C	-30
Flash Point °C	234
Total Base NO. mg KOH/g	10,5
Sulphated Ash, % m/m	1,0