



Quality, service, and customer satisfaction is our driving force.



AFRIQ AFRISTAR 5000 15W50 SL CF4

DESCRIPTION

Afristar 5000 is a semi-synthetic motor oil providing superior performance in today's passenger car engines.

This oil ensures excellent viscosity retention and superior engine protection under all modern driving conditions.

APPLICATION

- All naturally aspirated, fuel injected, turbocharged and multi-valve passenger car engines fuelled by either gasoline, diesel or LPG.

PERFORMANCE FEATURES

- **Excellent engine protection**
Provides excellent protection in today's efficient passenger car engines.
- **Catalyst and turbo proven**
Exceeds industry standards.
- **Fuel efficient**
Helps to improve fuel efficiency
- **Suitable for extended drain intervals**
Meets latest industry standards for use in applications where extended oil drain intervals are required.
- **Reduced chlorine content**
To meet environmental requirements – safer used oil disposal.

PERFORMANCE SPECIFICATIONS

MEETS OR EXCEEDS:

- API SL/CF4
- ACEA A3 AND B3-98
- JAPANESE ENGINES Qualified
- FORD MOTOR Co. M2C-153E
- VW NORM 500.00, 505.00
- MERCEDES-BENZ Sheet 229.1



TYPICAL PHYSICAL CHARACTERISTICS

SAE GRADE (J 300)	15W40
Kinematic Viscosity @ 40 ° C	141
@ 100 ° C (ASTM 445)	19.3
Viscosity Index (ISO 2909)	147
Density @ 15 ° C (ASTM D 4052)	0.886
Flash Point (PMCC), ° C (ISO 2592)	209
POUR POINT ° C (ISO 3016)	-27