



Quality, service, and customer satisfaction is our driving force.



AFRIQ HYDRAULIC ASHLESS 32, 46, 68

DESCRIPTION

This is a superior quality, ashless, high viscosity index, anti-wear hydraulic oil developed to meet the requirements of modern hydraulic systems. This high performance oil contains a balanced selection of nonzinc additives that afford anti-rust, oxidation stability, anti-foam and anti-wear properties.

APPLICATION

Is recommended for use in industrial hydraulic systems and also in other industrial applications where high quality oils are required. These include circulation systems and machine tools where high oxidation stability, anti-wear properties and high filtration speeds are of importance.

BENEFITS

- Superior wet and dry filterability.
- Excellent anti-wear performance.
- Good rust and corrosion protection.
- Outstanding oxidation stability.
- Fast air release.

PERFORMANCE LEVELS

- Denison HFO, HF-1, HF-2
- Vickers Eaton I-286-S; M-2950-S
- AFNOR NFE 48603 (HM)
- DIN 51524 Part I and II

KEY PROPERTIES

ISO Grade	32	46	68
Air Release @ 50 °C; min	5.0	6.7	8.6
Viscosity @ 40 °C	32	46	68
Viscosity Cst @ 100 °C	5.4	6.7	8.6
Viscosity Index	99	98	97
Flash Point °C (Min)	210	220	226
Pour Point °C (Max)	-33	-30	-24