



Quality, service, and customer satisfaction is our driving force.



AFRIQ MOULD RELEASE EM

DESCRIPTION

This is a Mould Release Emulsion that prevents concrete stitching to either the mould or shuttering form work. It produces a smooth finish on the concrete and keeps to mould a shuttering suitable for re-use. Excellent on moulds for pre-cast fencing and similar intricate shapes. It is a very thin non-staining, ready-to-use slightly oily, concrete emulsion mould release oil. It is custom made for each individual client thus the different lettering after the name. When used correctly it produces a high grade chemical shutter release for use on steel, wood, rubber and fiberglass moulds or shutters. This is a medium viscosity opaque white liquid. It has a neutral smell, and is not miscible with water.

APPLICATION

This product should be used neat. Application can be by brushing, spraying or swabbing, aiming at a concrete coverage with the thinnest possible film. New timber or moulds that have been wire brushed may require two or three applications before use. For subsequent use one application will be sufficient. An alternative conditioning method is one application of our SR7 Mould Conditioning Agent.

BENEFITS

- Adheres tenaciously to mould and shutters.
- Ensures that the mould or shuttering does not stick to the concrete.
- Easy application at all ambient temperatures.
- Provides a smooth finish.
- Protection of metal moulds from rust and corrosion.

KEY PROPERTIES

Density @20 °C KG L	0.862
Viscosity @ 40 °C	7
Flash Point °C	Non-Flash