



Quality, service, and customer satisfaction is our driving force.



AFRIQ ANTIFREEZE CONCENTRATE 95 %

DESCRIPTION

Afriq Antifreeze / summer coolant is a blend of M.E.G and a wide range of corrosion inhibitors for maximum protection when mixed with 50 % of water; it will lubricate the water pump, providing protection against extreme temperatures. Afriq Antifreeze can be used in cooling system of petrol and diesel engines, particularly those incorporating aluminium alloys up to – 36 °C.

APPLICATION

- Automotive
- Construction
- Earthmoving, quarrying and mining
- Agricultural equipment

BENEFITS

- Silicate free type inhibitor system provides exceptional protection.
- Protects all engines, cooling systems and metals such as iron, steel, aluminium, copper and solder alloys against corrosion.

PERFORMANCE LEVELS

MEET OR EXCEEDS:

- MB 325.3
- SABS 1251
- ADE PAGE 11
- ASTM D330
- SAE J1034
- Thermo King
- Navisor
- Freight Liner
- Caterpillar EC-1
- DAF
- Ford
- Jaguar
- Scania
- Isuzu
- Crysler
- VW and Audi
- Detroit Diesel
- Volvo Trucks
- Leyland
- Rover (Land Rover)



RECOMMENDED MIXTURE RATIOS

- 25 % Dilution - 12 °C
- 33 % Dilution - 18 °C
- 50 % Dilution - 36.5 °C

TYPICAL PHYSICAL CHARACTERISTICS

Colour ASTM	Blue
Density, KG/L @ 20 °C	1.133
Equilibrium Boiling Pt. (undiluted) °C	170
Freezing Pt (50 Vol % Solution) °C	-36.5
Ph, 50 % Vol Solution	7
Reserve Alkalinity ml O, 1N HCL	15
Setting Point °C	-45