



Quality, service, and customer satisfaction is our driving force.



AFRIQ EP 00

DESCRIPTION

EP 00 is a mineral-oil based polymer-thickened, stable, semi-fluid gear grease. It contains an anti-oxidant additive and also a sulphur-phosphorous type EP (extreme pressure) additive. It has characteristics that eliminate the risk of as excellent shear stability, load-carrying ability and the coating characteristics that eliminate the risk of dry start-up.

APPLICATION

This grease has been satisfactorily used by many industries. In South Africa in enclosed spur, bevel, helical and worm gearboxes. The operating temperature range is -10 °C to 100 °C.

ADVANTAGES

- Overcome leakage of lubricant
- Suitable for a wide range of gearbox applications, irrespective of the attitude in which the gearbox is mounted
- Eliminates dry start-up
- Allows extended maintenance periods
- Exhibits excellent shear stability, oxidation stability and load carrying ability
- Reduces noise
- Improves reliability

TYPICAL CHARACTERISTICS

Worked Penetration @ - 60 strokes	415
Nearest NLGI Classification	00
Timken O.K Load ((D-2509)	40
Thickener Type	Lithium 12 Hydroxystearate
Colour	Brown
Texture	Smooth
Dropping Point °F	300
Base Oil @ 40 °C	490
Rust Prevention (D1743)	Pass