



Quality, service, and customer satisfaction is our driving force.



AFRIQ COMPRESSOR OIL 32, 46, 68, 100 & 150

DESCRIPTION

Afriq Compressor Oil is a range of premium quality highly refined virgin paraffinic base oils. They contain a balanced additive system consisting of anti-wear, anti-rust, anti-oxidant and anti-foam additives to give outstanding levels of performance for use in reciprocating air, vane, rotary and piston compressors.

BENEFITS

- Outstanding overall performance
- Extended service intervals
- Excellent oxidation resistance
- Excellent corrosion inhibitors
- Excellent separation from water (IP19 and D1401)
- Excellent rust control even after water wash
- Resistance to sludge formation / filterability
- Ashless / calcium free

PERFORMANCE LEVELS

- Denison HFO, HF-1, HF-2
- Vickers Eaton I-286-5 Industrial Equipment
- Vickers Eaton M-2950-85 Mobile Equipment
- Cincinnati Machine P68, P69, P70
- Bosch Rexroth RE 90, 220
- DIN 51524 Part I, II and III
- ISO 11158 Categories HH, HL, HM and HV
- ASTM D6158-99

KEY PROPERTIES

TYPICAL PHYSICAL CHARACTERISTICS	32	46	68	100	150
Density @ 15 °C					0.885
Viscosity Cst @ 40 °C	32	46	68	100	150
Viscosity Cst @ 100 °C	5	7	8	9.8	15
Viscosity Index			98	97	101
Pour Point			-24	-21	-24
Flash Point °C	207	210	255	258	280

