



Quality, service, and customer satisfaction is our driving force.



AFRIQ ATF DX VI

DESCRIPTION

Afriq ATF DXVI is an exceptional automatic transmission fluid approved by General Motors for use in vehicle with automatic transmissions. This unique fluid is specially formulated to provide twice the service life of an ATF DX III and offers enhanced performance for both new and older transmissions. It is designed to protect your transmission through improved oxidation resistance, friction durability, shear stability and wear protection to help meet warranty protection requirements in late model vehicles. Designed to provide responsive shift feel throughout the life of the oil, **Afriq ATF DXVI** consistently protects your car/truck transmission longer than all previous DEXTRON type fluids.

APPLICATION

Afriq ATF DXVI is recommended for all 2006 and beyond GM vehicles with hydramatic automatic transmissions. It meets GM specification, GMN10060.

Always consult your vehicle owner's manual for specific recommendations.

BENEFITS

Extended fluid life:

- Extends life of the transmission.
- Potential to extend drain intervals.

Enhanced product performance for newer and older transmissions:

- Outstanding resistance against sludge and deposit formation.
- Improved oxidation and thermal stability versus ATF DX III.
- Superior anti-wear protection.
- Outstanding low temperature fluidity.
- Enhanced foam control which maintains responsive shifts and reduces wear on:
 - bearings;
 - bushing and
 - gears.

More consistent shifting performance:

- Optimized frictional properties.
- Prevents clutch shudder in modulated torque converters.
- Extended fluid and clutch durability.
- Smooth gear shifting during low temperature operation.
- Clutch plates and bands last longer.

Improved fuel economy versus ATF DX III:

- Improved torque transfer versus ATF DX III.
- More consistent viscosity profile which maintains a consistent torque performance.
- Lower viscosity versus ATF DX III.
- Improved shear stability.



TYPICAL PHYSICAL CHARACTERISTICS

PROPERTY	TEST METHOD	ATF DX VI
Colour	-	Red
Density, kg/l @ 15 °C	D4052	0.846
Flash Point, °C / °F	D92	206/403
Viscosity cSt @ 40 °C	D445	29.8
cSt @ 100 °C		6.0
Suplpated Ash, % wt	D874	0.02
Total Base No.	D2896	2.0
Qualification number		J-60001
Product ID code		DEX6
Viscosity Index	D2270	151
Pour Point °C / °F	D97	-54 / -65
Brookfield Viscosity cP @ -20 °C	D2983	1,053
cP @ -30 °C		3,164
cP @ -40 °C		12,030