

# AFRIQ IGO 68, 100, 150, 220, 320, 460, 680, 1000

#### **DESCRIPTION**

Afriq EP Industrial Gear Oils are superior performance gear lubes. Premium base oils with an effective sulphur-phosphorous EP additive system minimize wear of enclosed gears and other equipment operating under heavy loads and shock conditions.

These premium gear lubes utilize high viscosity index (HVI) base oils to provide high flash points, low volatility and superior oxidation stability. They provide outstanding protection in industrial gear sets operating under severe conditions, such as intermittent shock loads, high peak loads and heavy tooth loads.

These premium gear lubes utilize high viscosity index (HVI) base oils to provide high flash point.

## These quality extreme-pressure gear oils offer:

- Superior bearing protection
- Excellent anti-foam protection
- Excellent rust and corrosion protection
- Outstanding demulsibility characteristics
- Resistance to oxidative sludge and varnish
- Protection from galling, scuffing and welding of gear teeth

Afriq EP Industrial Gear Oils are ideal for heavy-loaded enclosed gear sets where extreme-pressure properties and adequate film strength are critical for industrial hypoid gear cases, as well as plain, ball, roller and sleeve type bearings. They may also be used for the lubrication of slides, ways, sprockets, chain drives, winches, hoist and machine tools.

### **PERFORMANCE LEVELS**

#### **MEETS OR EXEEDS:**

- US STEEL 224
- AGMA 250.04, 251.02
- DAWID BROWN \$1.53.101
- DIN 51517, PART 3
- CINCINNATI MACHINE



## **KEY PROPERTIES**

IGO	68	100	150	220	320	460	680	1000
Viscosity @ 40 ∘C	68	100	150	220	320	460	680	1000
Viscosity Cst @ 100  ∘C	8.7	11.4	15	19.4	25	30.8	38	43.8
Viscosity Index	100	100	100	100	100	97	92	84
Density @ 20 ∘C	0.887	0.891	0.897	0.899	0.903	0.904	0.912	0.931
Flash Point ∘C (Min)	191	193	196	199	202	204	204	205
Pour Point ∘C (Max)								
	-27	-27	-21	-18	-15	-9	-9	-9