



Quality, service, and customer satisfaction is our driving force.



MATERIAL SAFETY DATA SHEET

1. Chemical Product And Company Identification

Product Name	AFRIQ LUBE CUTTERBAR VIRGIN		
Product Use	Chainsaw Lubricant		
Manufacturer	Afriq Lube and Services cc P.O. Box 263708 Three Rivers 1935	016 424 4630 (t) 016 424 4651 (f) afriqlube@telkomsa.net (e)	

2. Composition / Information On Ingredients

Chemical Name	Cas- no.	Weight %	Symbol Codes	R-Phrase Numbers
Solvent-Refined Heavy Paraffinic Distillate	64741-88-4	>98.00	None	Not Applicable
Additives		<2.00	None	Not Applicable

See Section 15 for European Label Information
See Section 8 for Exposure Limits (if applicable)

3. Hazards Identification

Emergency response data:	Amber Liquid. DOT ERG No.- Not applicable
Potential health effects	
Note	No significant effects expected.

See Section 11 for further health effects / toxicological data

4. First Aid Measures

Inhalation	Not expected to be a problem. However, if respiratory irritation occurs due to excessive vapour or mist exposure, seek immediate medical assistance. If breathing has stopped, assist ventilation with mechanical device or use mouth-to-mouth resuscitation.
Skin contact	Remove contaminated clothing. Dry wipe and cleanse with hand cleaner, soap and water. Launder contaminated clothing before re-use. (See Section 16 – Injection Injury)
Eye Contact	Flush thoroughly with water. If irritation occurs call a doctor.



Ingestion	Not expected to be a problem. However, if discomfort occurs seek medical attention. Do not induce vomiting.
-----------	---

5. Fire-Fighting Measures

Extinguishing media	Carbon dioxide, foam, dry chemicals and water fog.
Special fire fighting procedure	Water or foam may cause frothing. Use water to keep fire exposed containers cool. Water spray may be used to flush spills away from exposure. Prevent runoff from fire control or dilution from entering streams, municipal sewers, or drinking water supply.
Special protective equipment for fire fighters	For fires in closed areas, fire fighters must use Self-Contained Breathing Apparatus.
Unusual fire/explosion hazards	None
Products of decomposition	Fumes, smoke, carbon monoxide, sulphur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.
Flash Point	>220 ° C (ASTM D-92)
Upper Explosion Limits	7.0 % (V)
Lower Explosion Limits	0.9 % (V)
NFPA Hazard ID	Health: 0; Flammability: 1; Reactivity: 0

6. Accidental Release Measures

Procedure if material is released or spilled	Report spills / release as required to appropriate authorities.
Methods for cleaning up	LAND SPILL: Shut off source taking normal safety precautions. Take measures to minimize the effects on the ground water. Recover by pumping using explosion-proof equipment or contain spilled liquid with sand or other suitable absorbent and remove mechanically into containers. If necessary, dispose of absorbed residues as directed in Section 13. WATER SPILL: Notify port and relevant authorities. Confine with booms in skimming equipment is available to recover the spill for a later recycling or disposal. Warn other ships in the vicinity. If allowed by regulatory authorities the use of suitable dispersants should be considered where recommended in local oil spill procedures.
Personal precautions	See Section 8
Environmental precautions	Prevent spill from entering municipal sewers, water sources or low lying areas. Advise the relevant authorities if contaminations have occurred.

7. Handling And Storage

Safe handling advice	No special precautions are necessary beyond normal good hygiene practices.
Storage information	Keep containers closed when not in use. Do not store in open or unlabelled containers. Do not store near sources, sparks, flames, strong oxidizing



Storage and handling procedures

agents and combustible materials.

Prevent small spills and leakages to avoid slip hazard.

8. Exposure Controls / Personal Protection

Occupational Exposure Limits (OELs)

Components	Cas- no.	Source	TWA	Value	Notations
Solvent-Refined Heavy Paraffinic Distillate	64741-88-4	ACGIH TVL	LTEL STEL	5mg/m ³ 10mg/m ³	Oil mists

LTEL

Long Term Exposures Limits- Time Weight Average (TWA) over 8 hours.

STEL

Short Term Exposure Limits- Time Weight Average (TWA) over 15 minutes.

Note

Limits Show for guidance only. Follow applicable regulations.

Personal Protection Equipment (PPE)

Engineering controls

If mists are generated, use ventilation, local exhaust or enclosures to control below exposure limits.

Respiratory protection

Approved respiratory equipment must be used when mist concentrations exceed the recommended exposure limits.

Eye protection

If splash with liquid is possible, chemical type goggles should be worn.

Skin and body protection

No special equipment required. However, if frequent slashing or liquid contact is likely to occur, wear oil impervious gloves and clothing. Good personal hygiene practices should always be followed.

9. Physical And Chemical Properties

Appearance	Liquid
Colour	Amber
Odour	Mild
Solubility	Negligible
Boiling point / range	>316 °C
Flash Point	>220 °C (ASTM D92)
Vapour Pressure	<0.1 hPa
Density	0.880 g/cm ³ @ 20 °C (ASTM D4052)
Viscosity, kinematic	14.5mm ² /s @ 100 °C (ASTM D445) 150mm ² /s @ 40 °C (ASTM D445)

10. Stability And Reactivity

Stability

Stable

Condition to avoid

Extreme heat.



Materials to avoid	Strong oxidizers
Hazardous decomposition products	Fumes, smoke, carbon monoxide, sulphur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

11. Toxicological Information

Acute oral toxicity	(Rats): Practically non-toxic (LD50: Greater than 2000 mg/kg). Based on testing of similar products and / or components.
Acute inhalation toxicity	(Rats): Practically non-toxic (LC50: Greater than 5 mg/l). Based on testing of similar products and / or components.
Acute dermal toxicity	(Rabbits): Practically non-toxic (LC50: greater than 2000mg/l). Based on testing of similar products and / or components.
Skin irritation	(Rabbits): Practically non-irritating. (Primary Irritation Index LC50: greater than 0.5 but less than 3). Based on testing of similar products and / or the components.
Eye irritation	(Rabbits): Practically non-irritating. (Draize score: greater than 6 but 15 or less). Based on testing of similar products and / or the components.
Repeated dose toxicity	Severely solvent refined and severely hydrotreated mineral base oils have been tested at an Environmental and Health Sciences Laboratory by dermal application to rats 5 days/week for 90 days at doses significantly higher than those expected during normal industrial exposure. Extensive evaluations including microscopic examination of internal organs and clinical chemistry of body fluids, showed no adverse effects.
Carcinogenicity	Chronic mouse skin painting studies of severely solvent refined mineral base oils showed no evidence of carcinogenic effects.
Other toxicological information	Overexposure to oil mist may result in oil droplet deposition and/or granuloma formation.

12. Ecological Information

Elimination information (persistence and durability)

Biodegradability	This product is expected to be inherently biodegradable.
Physic-chemical removability	Absorption to sediment and soil will be the predominant behaviour.
Bioaccumulation	Minimal owing to low water solubility
Eco toxicity effects	
Toxicity to aquatic organisms	This substance is practically non-toxic to aquatic organisms (LL50>1000 mg/l).
Further information on ecology	
Remarks	In the absence of specific environmental data for this product, this assessment is based on information for representative substances.



13. Disposal Considerations

Waste disposal	Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. Such burning may be limited pursuant to the Resource Conversation and Recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at any government approved waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.
Other regulations	The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

14. Transport Information

Note	This product is not regulated by the following: U.S DOT (CFR), ADR, IATA, and IMDG.
Static Accumulator (50 picosiemens or less)	Yes

15. Regulatory Information

US OSHA Hazard Communication Standard	When used for its intended purposes, this product is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.
Governmental Inventory	All components comply with TSCA, EINECS, AICS, METI, DSL, KECI, ENCS, PICCS and IECSC.
EU labelling	Product is not dangerous as defined by the European Union Dangerous Substances / Preparations Directives. EU labelling not required.
SARA	
U.S Superfund Amendments and Reauthorization Act SARA Title III	This product contains no "EXTREMELY HAZARDOUS SUBSTANCES".
SARA (311/312) Reportable Hazard Categories	None

The following product ingredient are cited on the list below

Chemical name	Cas- no.	Concentration (%)	List Citations
Solvent-Refined Heavy	64741-88-4	>98.00	Not Listed



Paraffinic Distillate			
Additives		<2.00	Not Listed

Regulatory List Searched

1=ACGIH ALL	6=IARC 1	11=TSCA 4	17=CA P65	22=MI 293
2=ACGIH A1	7=IARC 2A	12=TSCA 5a2	18=CA RTK	23=MN RTK
3=ACGIH A2	8=IARC 2B	13=TSCA 5e	19= FL RTK	24=NJ RTK
4=NTP CARC	9=OSHA CARC	14=TSCA 6	20=IL RTK	25=PA RTK
5=NTP SUS	10=OSHA Z	15=TSCA 12b	21=LA RTK	26=RI RTK

Code Key: CARS = Carcinogen; SUS = Suspected Carcinogen

16. Other Information

Note: Afriq Lube products do not contain PCBs.

Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. Information provided on this MSDS reflects intended use. This product should not be used for any other applications. In any case, the following advice should be considered:

FIRST AID	Wash skin with soap and water. Flush eyes with water. If overcome by fumes or vapour, remove to fresh air. If ingested do not induce vomiting. If any symptoms persist seek medical attention. Read and understand the MSDS before using this product.
INJECTION INJURY WARNING	If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.
SAFETY	Under normal conditions of intended use, this product does not pose a risk to health. Excessive exposure may result in eye, skin or irritation. Always observe good hygiene measures.

Disclaimer

Information given here in is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and we expressly disclaim all warranties of every kind of nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product. Nothing intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.

Prepared by	Product Safety Adviser Health, Safety, Environment and Quality Department Afriq Lube and Services cc 263 708 Three Rivers 1935
Prepared on	DECEMBER 2017



Telephone

| 016 424 4630 (Office hours)
| 079 010 7293 (After hours)