



Quality, service, and customer satisfaction is our driving force.



AFRIQ 5W40 SM/CF

DESCRIPTION

This is a semi-synthetic motor oil providing superior performance. It ensures excellent viscosity retention and superior engine protection under all modern driving conditions.

APPLICATION

All aspirated, fuel injected, turbocharged and multi-valve passenger car engines fuelled by either gasoline, diesel or LPG.

PERFORMANCE FEATURES

- **Excellent engine protection**
Provides excellent protection in today's efficient passenger car engines.
- **Catalyst and turbo proven**
Exceeds industry standards.
- **Fuel efficient**
Helps to improve fuel efficiency
- **Suitable for extended drain intervals**
Meets latest industry standards for use in applications where extended oil drain intervals are required.
- **Reduced chlorine content**
To meet environmental requirements – safer used oil disposal.

PERFORMANCE SPECIFICATIONS

MEETS OR EXCEEDS:

- API SM/CF
- ACEA A3 / B4-04
- JAPANESE ENGINES Qualified
- VW NORM 502.00, 505.00
- MERCEDES-BENZ Sheet 229.3
- BMW LL-98



TYPICAL PHYSICAL CHARACTERISTICS

GRADE	5W40
Kinematic Viscosity	
@ 40 ° C	79.1
@ 100 ° C	13.8
Viscosity Index	187
Density @ 15 ° C	0.85
Flash Point ° C	230
(PMCC)	
Pour Point ° C	-42