



Quality, service, and customer satisfaction is our driving force.



## AFRIQ 5W30 SM/CF

### DESCRIPTION

This is a semi-synthetic motor oil providing superior performance. It holds excellent viscosity retention and superior engine protection under all modern driving conditions.

### APPLICATION

All aspirated, fuel injected, turbocharged and multi-valve passenger car engines fuelled by either gasoline, diesel or LPG.

### PERFORMANCE FEATURES

- **Excellent engine protection**  
Provides excellent protection in today's efficient passenger car engines.
- **Catalyst and turbo proven**  
Exceeds industry standards.
- **Fuel efficient**  
Helps to improve fuel efficiency
- **Suitable for extended drain intervals**  
Meets latest industry standards for use in applications where extended oil drain intervals are required.
- **Reduced chlorine content**  
To meet environmental requirements – safer used oil disposal.

### PERFORMANCE SPECIFICATIONS

MEETS OR EXCEEDS:

- API SM/CF
- ACEA A3 / B4-04
- JAPANESE ENGINES Qualified
- FORD MOTOR Co. M2C-153E
- VW NORM 502.00, 505.00
- PEUGEOT-CITROEN – Meets requirements of PSA E-98 (level 2 for extended drain application)
- ROVER GROUP Registered
- MERCEDES-BENZ Sheet 229.3
- GM-LL-B-025



### TYPICAL PHYSICAL CHARACTERISTICS

SAE Grade	5W30
Kinematic Viscosity @ 40 ° C	70
@ 100 ° C	12
Viscosity Index	180
Density @ 15 ° C	0.85
Flash Point ° C	225
(PMCC)	
Pour Point ° C	-48