



Quality, service, and customer satisfaction is our driving force.



## AFRIQ 15W40 SL CF4

### DESCRIPTION

**Afriq 15W40 SL/CF** motor oil providing superior performance in today's modern engines. This oil ensures excellent viscosity retention and superior engine protection under all modern driving conditions.

### APPLICATION

All naturally aspirated, fuel injected, turbocharged and multi-valve engines fuelled by either gasoline, diesel or LPG.

### BENEFITS

- **Excellent engine protection**
  - Provides excellent protection in today's efficient passenger car engines.
- **Catalyst and turbo proven**
  - Exceeds industry standards.
- **Fuel efficient**
  - Helps to improve fuel efficiency
- **Suitable for extended drain intervals**
  - Meets latest industry standards for use in applications where extended oil drain intervals are required.
- **Reduced chlorine content**
  - To meet environmental requirements – safer used oil disposal.

### PERFORMANCE SPECIFICATIONS

Meets or Exceeds:

- API SL/CF4
- ACEA A3 AND B3-98
- JAPANESE ENGINES Qualified
- FORD MOTOR Co. M2C-153E
- VW NORM 500.00, 505.00
- MERCEDES-BENZ Sheet 229.1



## TYPICAL PHYSICAL CHARACTERISTICS

SAE GRADE (J 300)	15W40
Kinematic Viscosity @ 40 ° C	114
@ 100 ° C (ASTM 445)	14.5
Viscosity Index (ISO 2909)	110
Density @ 15 ° C (ASTM D 4052)	0.887
Flash Point (PMCC), ° C (ISO 2592)	209
POUR POINT ° C (ISO 3016)	-27