



Quality, service, and customer satisfaction is our driving force.



## AFRIQ 15W40 CG4 SL

### DESCRIPTION

With the ever increasing demands made on lubricants by the latest heavy duty, highly turbocharged engines, it became apparent that a new Super High Performance Diesel (SHPD) oil is required, SAE 15W40 was designed to fulfil this need. As an SAE 15W40 oil it may be used in most heavy duty diesel engines to combat bore polish and other wear related problems under severe operating conditions.

### APPLICATION

Afriq 15W40 CG4/SL is a premium mixed fleet, mineral based engine oil recommended for use in American, European and Japanese four stroke, direct injection (DI) and indirect injection diesel engines, both on and off-road and in a wide range of diesel and gasoline fuels. Afriq 15W40 CG4/SL has been designed to provide superior soot dispersancy, exceptional cleanliness and excellent oil consumption through the use of a unique combination of selected additives and base fluids. It is also recommended for use in all Detroit Diesel Two-stroke engines or Gardner naturally aspirated engines.

### PERFORMANCE LEVEL (API CG4 SL)

MEETS OR EXCEEDS:

- API CG4/SL
- ACEA A3 / B2 / E2-93
- MERCEDES BENZ 228.3 AND 228.1
- MAN M3725
- VOLVO VDS -3
- ALLISON C-4
- MEETS SABS 15, 161, 517
- GLOBAL DHD – 1
- CUMMINS CES 20078, CES 20071, 2 , 6, C5
- DAF ACEA E3
- HINO / ISUZU DH – 1
- MACK TRUCK EO – M, EO – M+
- RVI RID
- SCANIA LDF

### KEY PROPERTIES

SAE	15W40
-----	-------



Density at 20 °C	0.888
Viscosity at 40 °C	115
Viscosity at 100 °C	15
VI	132
TBN	11.2
Pour Point °C	-25
Flash Point °C	223
API	CG4/SL