



Quality, service, and customer satisfaction is our driving force.



AFRIQ EP 3 L GREASE

DESCRIPTION

Afriq EP 3 L Grease is a High-quality Multipurpose Lithium-based Grease from Solvent-refined oils and incorporating a multifunctional extreme pressure additive as well as corrosion and oxidation inhibitors. Afriq EP 3 L Grease is resistant to water and high-pressure steam and suitable for operating between -10 °C and 130 °C.

APPLICATION

Afriq EP 3 L Grease is designed for use in highly loaded plain and roller bearings as well as for shock loading conditions in steel mills. Suitable for use in the full range of bearing speeds encounter in electric motors, machine and woodworking tools, production equipment, textile and papermaking industry, generators and all types of vehicles. The smooth consistency makes these greases ideal for use in centralized lubrication systems and they can be used on ferrous and non-ferrous metals. Afriq EP 3 L Grease is recommended for all normal applications at ambient temperatures and where conditions are more severe with higher temperatures.

SPECIFICATIONS

Afriq EP 3 L Grease CONFORM TO sabs Specification1014.

TYPICAL CHARACTERISTICS

Thickening Agent	Lithium 12 Hydroxystearate
NLGI Classification	3
Worked Penetration @ 25 °C	220-250
Drop Point °C	180
Oil Viscosity @ 40 °C	90/110
Colour, Visual	Dark Brown
Recommended Temp. Range	120