



Quality, service, and customer satisfaction is our driving force.



AFRIQ 20W50 SJ CF4

DESCRIPTION

With the ever increasing demands made on lubricants by the latest heavy duty, highly turbocharged engines, it became apparent that new Super High Performance Diesel (SHPD) oil is required; 20W50 was designed to fulfil this need. As a 20W50 oil it may be used in most heavy duty diesel engines to combat bore polish and other wear related problems under severe operating conditions.

APPLICATION

Afriq 20W50 SJ/CF4 is a premium mixed fleet, mineral based engine oil recommended for use in American, European and Japanese four stroke, direct injection (DI) and indirect injection diesel engines, both on and off-road and in a wide range of diesel and gasoline fuels. Afriq 20W50 SJ/CF4 has been designed to provide superior soot dispersancy, exceptional cleanliness and excellent oil consumption through the use of a unique combination of selected additives and base fluids. It is also recommended for use in all Detroit Diesel four-stroke or Gardner naturally aspirated engines.

PERFORMANCE LEVEL (API CH4/SJ)

MEETS OR EXCEEDS:

- API CG4/SJ
- ACEA A3 / B2 / E2-93
- MERCEDES BENZ 228.3 AND 228.1
- MAN M3725
- VOLVO VDS -3
- ALLISON C-4
- GLOBAL DHD – 1
- CUMMINS CES 20078, CES 20078, 71,2,6
- DAF ACEA E3
- HINO / ISUZU DH – 1
- MACK TRUCK EO – M
- RVI RID
- SCANIA LDF



KEY PROPERTIES

SAE	20W50
Density at 20 °C	0.894
Viscosity at 40 °C	158
Viscosity at 100 °C	17.8
VI	139
TBN	9.8
Pour Point °C	-22
Flash Point °C	250
API	SJ/CF4