



Quality, service, and customer satisfaction is our driving force.



AFRIQ HD OPEN GEAR L/C 2 EP 1020 M

DESCRIPTION

Afriq HD Open Gear L/C 2 EP 1020 M is tenacious extreme pressure, lithium calcium greases giving excellent water repelling properties and in combination with a high viscosity base oil, enhances lubricity and load carrying capacity.

The high content of a synergistic solid lubricant combination gives an excellent load carrying and anti-wear characteristic.

APPLICATION

Afriq HD Open Gear L/C 2 EP 1020 M has been specially developed for applications where the combination of loads, medium to slow speeds and water washout exclude the use of conventional products.

Afriq HD Open Gear L/C 2 EP 1020 M is recommended for the lubrication of large size spherical roller bearings subject to high load and slow rotations, a situation where micro slip is likely to occur. The typical applications are trunnion bearings on rotating drums, support and thrust rollers on rotary kilns and dryers, slewing ring bearings, high pressure roller mills and crushers.

TYPICAL PHYSICAL CHARACTERISTICS

	EP 2
Thickening agent	Li Ca
NLGI Classification	2
Worked penetration @ 25°C	265 - 295
Drop point °C	> 180
Timken OK Load kg.	25
Oil viscosity @ 40°C Cst	1020
Temperature Range	-10 - 120°C