



Quality, service, and customer satisfaction is our driving force.



AFRIQ AUTOMATIC TRANSMISSION FLUID DX II

DESCRIPTION

ATF is an automatic transmission fluid for use where manufacturers call for a Dextron II fluid. It is blended from virgin base oils, which have been fortified with anti-wear, anti-oxidant, anti-foam, anti-corrosion and viscosity index improvers together with friction modifiers. This blend component gives high levels of performance and long service life.

APPLICATION

- Automotive automatic transmissions
- Power shift transmissions
- Power steering units
- Hydraulic power systems

PERFORMANCE LEVELS

MEETS OR EXCEEDS:

- DEXTRON II D
- ALLISON C4
- MAN 339 TYPE Z-1 AND TYPE V-1
- VOLVO 97335 AND 97325
- MERCEDES BENZ SHEET 236.1 AND 236.5
- ZF SHEET TE-ML 02F, 03D, 04D, 14A, 17C
- ZF TE-ML-09
- VOITH 55.6335
- FORD'S MERCON ATF SPECIFICATIONS
- CATERPILLAR TO-2 REQUIREMENTS
- GENERAL MOTORS TYPE A SUFFIX A (TASA)
- GENERAL MOTORS DEXTRON II E

BENEFITS

Excellent anti-wear properties ensure longer equipment life.

KEY PROPERTIES

TYPICAL PHYSICAL CHARACTERISTICS	
Viscosity @ 40 C	34.6
Viscosity Cst @ 100 C	7
Viscosity Index	140
Pour Point C (Max)	-42
Flash Point C (Min)	193