

MATERIAL SAFETY DATA SHEET

1. Chemical Product And Company Identification

Product Name AFRIQ LUBE LEP 2N

Product Use Industrial Grease

Manufacturer Afriq Lube and Services cc 016 424 4630 (t)

P.O. Box 263708 016 424 4651 (f)

Three Rivers <u>afriqlube @telkomsa.net</u> (e)

1935

2. Composition / Information On Ingredients

Chemical Name	Cas- no.	Weight %	Symbol Codes	R-Phrase Numbers
Lithium 12-hydroxystearate	7260-77-7	<5.00		
Zinc Naphthenate	12001-85-3	<5.00	Xi	R36/38, R52/53

See Section 15 for European Label Information See Section 8 for Exposure Limits (if applicable)

3. Hazards Identification

Emergency response data: Light Brown. Material is combustible. DOT ERG No.- Not

applicable

Potential health effects

Note Under normal conditions of intended use, this product does not

pose a risk to health. Excessive exposure may result in eye, skin

and respiratory irritation.

Skin Repeated or excessive exposure may cause skin dryness or

cracking.

Potential environmental effects This product is not readily biodegradable.

See Section 11 for further health effects / toxicological data

4. First Aid Measures

Inhalation Under certain conditions smoke may be generated. Remove victim from

further exposure.

Skin contact Wash contact areas with soap and water.

Eye Contact Flush thoroughly with water. If irritation occurs call a doctor.



Ingestion

Not expected to be a problem. However, if discomfort occurs seek medical attention. Do not induce vomiting.

5. Fire-Fighting Measures

Extinguishing media Carbon dioxide, foam, dry chemicals and water fog.

Special fire fighting procedure

Water or foam may cause frothing. Use water to keep fire exposed containers cool. Water spray may be used to flush spills away from exposure. Prevent runoff from fire control or dilution from entering streams, municipal sewers, or drinking water supply.

Special protective equipment for fire fighters

For fires in closed areas, fire fighters must use Self-Contained Breathing Apparatus.

Products of decomposition

Fumes, smoke, carbon monoxide, sulphur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

NFPA Hazard ID

Health: 0; Flammability: 1; Reactivity: 0

6. Accidental Release Measures

Procedure if material is released or spilled

Report spills / release as required to appropriate authorities.

Methods for cleaning up

LAND SPILL: Shut off source taking normal safety precautions. Take measures to minimize the effects on the ground water. Recover by pumping using explosion-proof equipment or contain spilled liquid with sand or other suitable absorbent and remove mechanically into containers. If necessary, dispose of absorbed residues as directed in Section 13.

WATER SPILL: Notify port and relevant authorities. Confine with booms in skimming equipment is available to recover the spill for a later recycling or disposal.

Environmental precautions

Prevent spill from entering municipal sewers, water sources or low lying areas. Advise the relevant authorities if contaminations have occurred.

Personal precautions

See section 8

7. Handling And Storage

Safe handling advice

High pressure injection under the skin may occur due to the rupture of pressurised lines. (See Section 16 – Injection Injury)

Storage information

Keep containers closed when not in use. Do not store in open or unlabelled containers. Do not store near sources, sparks, flames, strong oxidizing agents and combustible materials.

Storage and handling procedures

Prevent small spills and leakages to avoid slip hazard.

8. Exposure Controls / Personal Protection



Occupational Exposure Limits (OELs)

Components	Cas- no.		Source	TWA	Value		Notations
LTEL		Long Term Exposures Limits- Time Weight Average (TWA) over 8 l				over 8 hours.	
STEL		Short Term Exposure Limits- Time Weight Average (TWA) over 15 minutes					
Note		Limits Shown for guidance only. Follow applicable regulations.				ns.	

Personal Protection Equipment (PPE)

Engineering controls

Use in well-ventilated area.

No special requirements under ordinary conditions of use and with adequate ventilation.

Eye protection

If eye contact is likely, normal industrial eye protection practices should be employed.

Skin and body protection

If prolonged or repeated skin contact is likely, wear oil impervious gloves and clothing. Good personal hygiene practices should always be followed.

9. Physical And Chemical Properties

Appearance	Semi Solid
Colour	Grey Brown
Base component	Lithium Grease
Odour	Characteristic
Solubility	Immiscible

10. Stability And Reactivity

Stability

Condition to avoid

Extreme heat and high energy sources of ignition, such as sparks and static electricity.

Materials to avoid

Strong oxidizers

Hazardous decomposition products

Fumes, smoke, carbon monoxide, sulphur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

11. Toxicological Information

Acute oral toxicity

(Rats): Practically non-toxic (LD50: Greater than 2000 mg/kg). Based on testing of similar products and / or components.

(Rats): Practically non-toxic (LC50: Greater than 5 mg/l). Based on testing of similar products and / or components.

(Rabbits): Practically non-toxic (LC50: greater than 2000mg/l). Based on testing of similar products and / or components.



Skin irritation (Rabbits): Practically non-irritating. (Primary Irritation Index LC50: greater

than 0.5 but less than 3). Based on testing of similar products and / or the

components.

Eye irritation (Rabbits): Practically non-irritating. (Draize score: greater than 6 but 15 or

less). Based on testing of similar products and / or the components.

Sensitization Not expected to be sensitizing based on tests of this product, components,

or similar products.

Repeated dose toxicity No significant adverse effects were found in studies using repeated dermal

applications of similar formulations to the skin of laboratory animals for 13 weeks at doses significantly higher than those expected during normal industrial exposure. The animals were evaluated extensively for effects of exposure (haematology, serum chemistry, urinalysis, organ weights,

microscopic examination of tissues etc.).

Carcinogenicity Repeated and / or prolonged exposure may cause irritation to the skin, eyes

or respiratory tract. Mineral base oils are severely solvent refined and severely hydrotreated. Chronic mouse skin painting studies of severely

treated oils showed no evidence of carcinogenic effects.

Other toxicological

information

No significant effects expected.

12. Ecological Information

Elimination information (persistence and durability)

Biodegradability This product is not inherently biodegradable...

Physic-chemical removability | Not established.

Bioaccumulation Not established.

Eco toxicity effects

Further information on ecology

Remarks

The major components in the formulation show no aquatic toxicity at 1000 mg/L loading; therefore long-term adverse effects in the aquatic

environment are not expected.

13. Disposal Considerations

Waste disposal Product is suitable for burning in an enclosed, controlled burner for fuel

value or disposal by supervised incineration. Such burning may be limited pursuant to the Resource Conversation and Recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at any government approved waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

Contaminated packaging

Empty containers retain residue (liquid and / or vapour) and can be



dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Other regulations

The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

14. Transport Information

15. Regulatory Information

US OSHA Hazard Communication Standard

When used for its intended purposes, this product is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

Governmental Inventory

All components comply with TSCA, EINECS, AICS, METI, DSL, KECI, ENCS, PICCS and IECSC.

EU labelling

Product is not dangerous as defined by the European Union Dangerous Substances / Preparations Directives. EU labelling not required.

SARA

U.S Superfund Amendments and Reauthorization Act SARA Title III This product contains no "EXTREMELY HAZARDOUS SUBSTANCES".

SARA (311/312) Reportable Hazard Categories

None

The following product ingredient are cited on the list below

Chemical name	Cas- no.	Concentration (%)	List Citations
Lithium 12- hydroxystearate	7260-77-7	<5.00	22
Zinc Naphthenate	12001-85- 3	<5.00	

Regulatory List Searched

1=ACGIH ALL 6=IARC 1 11=TSCA 4 17=CA P65 22=MI 293



2=ACGIH A1 7=IARC 2A 12=TSCA 5a2 18=CA RTK 23=MN RTK 8=IARC 2B 19= FL RTK 3=ACGIH A2 13=TSCA 5e 24=NJ RTK 4=NTP CARC 9=OSHA CARC 14=TSCA 6 20=IL RTK 25=PA RTK 5=NTP SUS 10=OSHA Z 15=TSCA 12b 21=LA RTK 26=RI RTK

Code Key: CARS = Carcinogen; SUS = Suspected Carcinogen

16. Other Information

Note: Afriq Lube products do not contain PCBs.

Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. Information provided on this MSDS reflects intended use. This product should not be used for any other applications. In any case, the following advice should be considered:

FIRST AID Wash skin with soap and water. Flush eyes with water. If overcome by

fumes or vapour, remove to fresh air. If ingested do not induce vomiting. If any symptoms persist seek medical attention. Read and understand the

MSDS before using this product.

INJECTION INJURY If product is injected into or under the skin, or into any part of the body,

WARNING regardless of the appearance of the wound or size, the individual should be

evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly

reduce the ultimate extent of injury.

SAFETY Under normal conditions of intended use, this product does not pose a risk

to health. Excessive exposure may result in eye, skin or irritation. Always

observe good hygiene measures.

Disclaimer

Information given her in is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and we expressly disclaim all warranties of every kind of nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product. Nothing intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.

Prepared by Product Safety Adviser

Health, Safety, Environment and Quality Department

Afriq Lube and Services cc 263 708 Three Rivers 1935

Prepared on JANUARY 2018

Telephone 016 424 4630 (Office hours)

079 010 7293 (After hours)