



Quality, service, and customer satisfaction is our driving force.



AFRIQ BRAKE FLUID DOT 3

DESCRIPTION

Afriq Brake Fluid Dot 3 is a non-mineral fluid designed for medium to high temperature operating conditions encountered in automotive vehicles fitted with hydraulic brake and clutch systems.

ADVANTAGES

- Formulated using Glycol ethers and polyglycols.
- Contains complex corrosion and oxidation inhibitors to enhance corrosion resistance and chemical stability.
- Suitable for hydraulic systems employing both synthetic and natural rubber cups and seals.
- Correct viscosity for instant flow and even braking.
- Excellent lubrication ensuring minimum wear of rubber cups and moving parts of master and wheel cylinders.
- Compatible with other brake fluids.

APPROVALS / PERFORMANCE LEVELS

U.S. Dept of Transport D.O.T. 3: S.A.E J1703: Compulsory South African Standard Specification.

PROPERTIES

Test	Typical Property
Density @ 20 °C	1.033
Viscosity @ 40 °C cst	8.16
Viscosity @ 100 °C cst	2.11
Viscosity @ - 40 CP MAX	1500
Boiling Point °C	270
Flash Point °C	144
Colour	Pale Amber

NOTE: Always handle with utmost cleanliness, replace cap immediately and firmly after use. Will damage paint finishes, so prevent spillage.