



Email: afriqlube@telkomsa.net
Tel: 016 424 4630 / 079 010 7293
Fax: 016 424 4651 / 086 590 2986
Vat: 4700254289
Reg: 2009/199579/23
www.afriqlube.co.za

AFRIQ LUBE & SERVICES CC.

AFRIQ BRAKE FLUID DOT 4

DESCRIPTION

Afriq Brake Fluid Dot 4 is heavy duty synthetic brake fluid blended mainly from glycol ethers and poly-glycols and contains corrosion and oxidation inhibitors to enhance its natural corrosion and chemical stability. It exceeds the two internationally recognised American Standards, viz., SAE J1703 and DOT 4 (Department of Transportation, USA). It also exceeds the requirements of the South African Government's Compulsory Standard Specification (Gazette No. 4562) and passes all important tests specified for brake fluids, e.g. fluidity at low temperatures, evaporation, water tolerance, compatibility, resistance to oxidation and effect on rubber.

APPLICATION

Afriq Brake Fluid Dot 4 is recommended for use in both disc and drum brake systems requiring both DOT 3 and DOT 4 fluids. It is also used in clutch hydraulic systems.

PERFORMANCE LEVEL

SAE J 1703, DOT 4, S.A. Government mandatory requirements.

BENEFITS

- Firm braking pressure under all service conditions
- Excellent chemical stability and freedom from gummy deposits
- High boiling point to prevent vapour forming in brake systems
- Protects metals and rubbers used in hydraulic brake and clutch systems
- Compatible with other brake fluids meeting Compulsory Government Standards

TYPICAL PHYSICAL CHARACTERISTICS

| | |
|------------------------|------|
| Viscosity @ -40 °C cst | 1100 |
| Viscosity @ 100 °C cst | 1.5 |
| Dry Boiling Point, °C | 275 |

NOTE: South African Government's Compulsory Standard Specification calls for a minimum Dry Point of 230 °C.